

# QUANTUM T280

**sikkens**

WOOD COATINGS

INTERIOR

## TECHNOLOGY

PU Acrylic

## PRODUCT TYPE

Topcoat

## PRODUCT DESCRIPTION

Lightfast solventborne 2K topcoat with high scratch resistance, as well as resistance to chemicals and heat. On light wood, this product has sun blocking properties. Application by brush, roller or spray. Can be used as a final finish for QuantumColor QC-T460\_xx.

- high scratch resistance
- chemical and heat resistance
- sun blocking on light wood
- closed and open pores
- non yellowing
- lightfast in all conditions



## COLOUR

Clear

## GLOSS LEVEL

15 / 30

## PACK SIZES

QT280-1 - 5 L  
QT280-2 - 20 L

## SHELF LIFE

24 months

## STORAGE CONDITIONS

Keep cans tightly sealed, in a well ventilated place, with controlled temperature between 10 and 30°C

## SOLID CONTENT

27% -28% ±1% depending on gloss level

## DENSITY (SPECIFIC WEIGHT)

0.94 - 0.95 +/- 1% depending on gloss level

## DELIVER VISCOSITY

25 ± 2 Viscosity at delivery DIN 4 mm

## PREPARATION OF SUBSTRATES



Raw wooden surfaces. Graduated sanding of wood. Carefully remove the sanding dust. Coarse-pore wood must be brushed out

P120,  
P150,  
P180

## HARDENER

Hardener	Ratio (by weight)
HPU6300	10%

## THINNING

TPU 9300-F, Fast drying  
TPU 9301-S, Slow drying

## APPLICATION METHOD

Spray application airmix/airless, spray application high/low pressure

## APPLICATION

Spray pressure (bar)	1.5 - 2.0	110 - 130
Nozzle size (mm)	1.6 - 2.0	0.23 - 0.28
Thinner to be added (%)	0-20	0 - 20
Processing viscosity DIN 4mm (sec.)	20	20
Layer Thickness (g/m <sup>2</sup> )	100 - 120	100 - 120

Products from AkzoNobel Wood Coatings are exclusively produced for professional and industrial users, who have a basic knowledge of the handling and application of chemical/technical products for surface design. The processing instructions for reaching the qualities given in the leaflets should be regarded as non-binding recommendations and do not constitute any warranty. These recommendations are based on our experiences, including test series, and should facilitate and promote the work of our clients. Any potential deviation from ideal working conditions is within the responsibility of our clients and may affect the (end) result of the application. The purchaser is not relieved from his duties to inspect the product and its suitability for the surface to be processed, preferably through trial processing. If in any doubt as to the handling or processing of the purchased product, our material experts as well as our application and laboratory technicians will help you to the best of their ability.

AkzoNobel, of course, guarantees an impeccable quality of its products in its product specifications, yet the use thereof lies entirely within the responsibility of the purchaser. As long as we have not guaranteed - in writing - the specific characteristics and suitability of a product for a contractually agreed purpose, any advice or information given regarding the application or handling, even if the advice or information is given to the best of our knowledge, will not be binding nor will it constitute a warranty. AkzoNobel's liability for the use of its products by its customers is limited in its

General Sales and Delivery Conditions, to which the purchaser is hereby referred. The applicable version of the Technical Data Sheet for this product can be downloaded from our websites. Previous versions of the Technical Data Sheets are rendered void with the issue of a new one. Date of issue: 2026-05-07 / 19

# QUANTUM T280

**sikkens**


WOOD COATINGS

INTERIOR

## DRYING TIME @ 20°C

Dust dry	At least 20 minutes
Touch dry	At least 1 hour
Ready for transport	At least 12 hours
Sandable	At least 2 hours

## TEST STANDARDS

	DIN 68861/1B Chemical exposure of furniture surfaces
---	--

Products from AkzoNobel Wood Coatings are exclusively produced for professional and industrial users, who have a basic knowledge of the handling and application of chemical/technical products for surface design. The processing instructions for reaching the qualities given in the leaflets should be regarded as non-binding recommendations and do not constitute any warranty. These recommendations are based on our experiences, including test series, and should facilitate and promote the work of our clients. Any potential deviation from ideal working conditions is within the responsibility of our clients and may affect the (end) result of the application. The purchaser is not relieved from his duties to inspect the product and its suitability for the surface to be processed, preferably through trial processing. If in any doubt as to the handling or processing of the purchased product, our material experts as well as our application and laboratory technicians will help you to the best of their ability.

AkzoNobel, of course, guarantees an impeccable quality of its products in its product specifications, yet the use thereof lies entirely within the responsibility of the purchaser. As long as we have not guaranteed - in writing - the specific characteristics and suitability of a product for a contractually agreed purpose, any advice or information given regarding the application or handling, even if the advice or information is given to the best of our knowledge, will not be binding nor will it constitute a warranty. AkzoNobel's liability for the use of its products by its customers is limited in its

General Sales and Delivery Conditions, to which the purchaser is hereby referred. The applicable version of the Technical Data Sheet for this product can be downloaded from our websites. Previous versions of the Technical Data Sheets are rendered void with the issue of a new one. Date of issue: 2026-05-07 / 19