

TECHNOLOGY

Waterborne

PRODUCT TYPE

Additive

PRODUCT DESCRIPTION

Waterborne, ready-to-use product for the pre-treatment of raw wood prior to the staining process. The product is used as preliminary stain for the balancing of colours. For all types of wood, especially those with different absorption behaviour (solid or veneered). Especially in the case of veneer with butt joints, different absorption behaviour of the veneer occurs that can be minimized by pre-treatment with this product.



PACK SIZES

5261314 - 1 L

SHELF LIFE

12 months in original, unopened package

STORAGE CONDITIONS

Between 15 and 25°C under clean and dry conditions.


SOLID CONTENT

2%

DENSITY (SPECIFIC WEIGHT)

1,00

PREPARATION OF SUBSTRATES

	Graduated sanding of wood Carefully remove the sanding dust. Coarse-pore wood must be brushed out.	P120, P150, P180
---	--	------------------------

APPLICATION METHOD

Shake or stir well before use. Richly apply the product with a brush, a roller or a spray gun. Smoothen with fine sanding paper P400 after drying overnight. Do not sand through.

DRYING TIME @ 20°C

Sandable	At least 12 hours
----------	-------------------

GENERAL INSTRUCTION

Aftertreatment:
Further treatment with solvent-based or waterborne Sikkens® stains. Please see the separate Technical Data Sheets for these products.

Products from AkzoNobel Wood Coatings are exclusively produced for professional and industrial users, who have a basic knowledge of the handling and application of chemical/technical products for surface design. The processing instructions for reaching the qualities given in the leaflets should be regarded as non-binding recommendations and do not constitute any warranty. These recommendations are based on our experiences, including test series, and should facilitate and promote the work of our clients. Any potential deviation from ideal working conditions is within the responsibility of our clients and may affect the (end) result of the application. The purchaser is not relieved from his duties to inspect the product and its suitability for the surface to be processed, preferably through trial processing. If in any doubt as to the handling or processing of the purchased product, our material experts as well as our application and laboratory technicians will help you to the best of their ability.

AkzoNobel, of course, guarantees an impeccable quality of its products in its product specifications, yet the use thereof lies entirely within the responsibility of the purchaser. As long as we have not guaranteed - in writing - the specific characteristics and suitability of a product for a contractually agreed purpose, any advice or information given regarding the application or handling, even if the advice or information is given to the best of our knowledge, will not be binding nor will it constitute a warranty. AkzoNobel's liability for the use of its products by its customers is limited in its

General Sales and Delivery Conditions, to which the purchaser is hereby referred. The applicable version of the Technical Data Sheet for this product can be downloaded from our websites. Previous versions of the Technical Data Sheets are rendered void with the issue of a new one. Date of issue: 2025-12-15 / 8