OILED AND WAXED FLOOR 2-IN-1 CARE

sikkens
WOOD COATINGS
INTERIOR

TECHNOLOGY

Natural

PRODUCT TYPE

Care

PRODUCT DESCRIPTION

Care product with special natural waxes.
For the care and refreshment of all oiled and waxed floors and stairs.



PACK SIZES

OWFC - 1 L

SHELF LIFE

12 months in original, unopened package

STORAGE CONDITIONS

Keep cans tightly sealed, i a well ventilated place, with controlled temperature between 10 and 30°C

DENSITY (SPECIFIC WEIGHT)

1,01 +/- 1%

PREPARATION OF SUBSTRATES



First thoroughly remove dirt from the floor by means of vacuuming. In case the floor should be extremely dirty, it must first be cleaned with FLOOR SUPER CLEANER

APPLICATION METHOD

The product is ready for use. The floor is evenly treated with a slightly damp lint-free cloth. After 90 minutes, the surface can optionally be polished with a coarse cotton cloth. By doing so, the surface is slightly polished and appears to be shinier. Never use water for after-treatment

GENERAL INSTRUCTION

Aftertreatment:
Depending on wear and visual appearance, caring of

oiled and waxed Sikkens surfaces must be repeatedseveral times a year after the surface has been cleaned.
A renovation with the originally used Sikkens Care Product may be necessary in case of heavy wear of the surface treated with Sikkens Care Products.

Products from AkzoNobel Wood Coatings are exclusively produced for professional and industrial users, who have a basic knowledge of the handling and application of chemical/technical products for surface design. The processing instructions for reaching the qualities given in the leaflets should be regarded as non-binding recommendations and do not constitute any warranty. These recommendations are based on our experiences, including test series, and should facilitate and promote the work of our clients. Any potential deviation from ideal working conditions is within the responsibility of our clients and may affect the (end) result of the application. The purchaser is not relieved from his duties to inspect the product and its suitability for the surface to be processed, preferably trough trial processing. If in any doubt as to the handling or processing of the purchased product, our material experts as well as our application and laboratory technicians will help you to the best of their ability.

AkzoNobel, of course, guarantees an impeccable quality of its products in its product specifications, yet the use thereof lies entirely within the responsibility of the purchaser. As long as we have not guaranteed – in writing – the specific characteristics and suitability of a product for a contractually agreed purpose, any advice or information given regarding the application or handling, even if the advice or information is given to the best of our knowledge, will not be binding nor will it constitute a warranty. AkzoNobel's liability for the use of its products by its customers is limited in its

General Sales and Delivery Conditions, to which the purchaser is hereby referred. The applicable version of the Technical Data Sheet for this product can be downloaded from our websites. Previous versions of the Technical Data Sheets are rendered void with the issue of a new one. Date of issue: 2026-10-13 / 14

Akzo Nobel Hilden GmbH, Düsseldorfer Str. 96 - 100, 40721 Hilden, Germany.
www.sikkens-wood-coatings.com

AkzoNobel