

FLOOR MIXING PUTTY

sikkens

WOOD COATINGS

INTERIOR

TECHNOLOGY

Waterborne

PRODUCT TYPE

Additive

PRODUCT DESCRIPTION

Waterborne solution for mixing with sanding dust to make a filler.

- closes joints in holes
- reduces lateral glueing
- easy to be applied
- quick drying and easily sandable



PACK SIZES

5 L

SHELF LIFE

12 months

STORAGE CONDITIONS

Keep cans tightly sealed, in a well ventilated place, with controlled temperature between 10 and 30°C

SOLID CONTENT

34.3% ± 1%

DENSITY (SPECIFIC WEIGHT)

1,05 +/- 1%

DELIVER VISCOSITY

20 ± 2 Viscosity at delivery DIN 4 mm

PREPARATION OF SUBSTRATES

	New, untreated floors: Depending on the type of wood and the way of installation, basic sanding must be carried out. Thoroughly remove dirt from the floor by means of vacuuming.	P80 to max. P120
	Renovation of already coated wooden floors: First carry out basic sanding to remove the old lacquer film completely. Thoroughly remove dirt from the floor by means of vacuuming.	P80 to max. P120

DRYING TIME @ 20°C

Sandable	At least 45 minutes
----------	---------------------

Products from AkzoNobel Wood Coatings are exclusively produced for professional and industrial users, who have a basic knowledge of the handling and application of chemical/technical products for surface design. The processing instructions for reaching the qualities given in the leaflets should be regarded as non-binding recommendations and do not constitute any warranty. These recommendations are based on our experiences, including test series, and should facilitate and promote the work of our clients. Any potential deviation from ideal working conditions is within the responsibility of our clients and may affect the (end) result of the application. The purchaser is not relieved from his duties to inspect the product and its suitability for the surface to be processed, preferably through trial processing. If in any doubt as to the handling or processing of the purchased product, our material experts as well as our application and laboratory technicians will help you to the best of their ability.

AkzoNobel, of course, guarantees an impeccable quality of its products in its product specifications, yet the use thereof lies entirely within the responsibility of the purchaser. As long as we have not guaranteed – in writing – the specific characteristics and suitability of a product for a contractually agreed purpose, any advice or information given regarding the application or handling, even if the advice or information is given to the best of our knowledge, will not be binding nor will it constitute a warranty. AkzoNobel's liability for the use of its products by its customers is limited in its

General Sales and Delivery Conditions, to which the purchaser is hereby referred. The applicable version of the Technical Data Sheet for this product can be downloaded from our websites. Previous versions of the Technical Data Sheets are rendered void with the issue of a new one. Date of issue: 2023-01-09 / 7