







Product description		Aftertreatment	
Description	For the preparation of waxed high-quality wood surfaces.		
Range of application			
Description	Almost all types of wood in the interior. For example wood and cork flooring, furniture, worktops, wooden ceilings, wood paving, industrial parquet, stairs, etc. When used on strained surfaces such as dining tables, floors, stairs, etc., previous treatment with Naturtrend oils is required.		
Product data			
Product code		NHW	
Packaging size		500 ml 2.5 l	
Viscosity at delivery		pasty	
Shelf life – Original container unopened		at least 2 years	
Preparation of substrates			
	Raw wooden surfaces. Furniture	P180, P240, P320	
	wear-resistant surfaces of wooden furniture and floors and stairs	First, treat with deeply penetrating Naturtrend oils.	
Processing			
	The product is applied by means of a brush (not too soft), a bale of cloth or by hot-spraying. (max. 80°C) The furniture surface is brushed to shine after the indicated drying time. Floors are brushed to shine with a white, fine pad or a lambskin disc.		
			
			
Application			
Yield (m²/500 ml)		15-30	
Drying time @ 20°C			
Polishable		at least 3 hours	
First, light load		at least 24 hours	
Full strength, ready to walk on		at least 3 days	

Products from AkzoNobel Wood Coatings are exclusively produced for professional and industrial users, who have a basic knowledge of the handling and application of chemical/technical products for surface design. The processing instructions for reaching the qualities given in the leaflets should be regarded as non-binding recommendations and do not constitute any warranty. These recommendations are based on our experiences, including test series, and should facilitate and promote the work of our clients. Any potential deviation from ideal working conditions is within the responsibility of our clients and may affect the (end) result of the application. The purchaser is not relieved from his duties to inspect the product and its suitability for the surface to be processed, preferably through trial processing. If in any doubt as to the handling or processing of the purchased product, our material experts as well as our application and laboratory technicians will help you to the best of their ability. AkzoNobel, of course, guarantees an impeccable quality of its products in its product specifications, yet the use thereof lies entirely within the responsibility of the purchaser. As long as we have not guaranteed – in writing – the specific characteristics and suitability of a product for a contractually agreed purpose, any advice or information given regarding the application or handling, even if the advice or information is given to the best of our knowledge, will not be binding nor will it constitute a warranty. AkzoNobel's liability for the use of its products by its customers is limited in its General Sales and Delivery Conditions, to which the purchaser is hereby referred. The applicable version of the Technical Data Sheet for this product can be downloaded from our websites. Previous versions of the Technical Data Sheets are rendered void with the issue of a new one. Date of issue: 2024-08-26 / 16