Intensiv Cleanser IR









Product description

Description

Description

Waterborne cleaning agent. Can be applied diluted and undiluted.

Range of application

For the cleaning of floors such us parquet, plastic, cork, PVC, linoleum, natural stone, artificial stone, tile, rubber floors etc. For the basic cleaning of waxed and oiled floors before they are newly coated. Cleaning of painting equipment and accessories after the application of waterborne Zweihorn® paints / varnishes or Naturtrend products. Removes old self-lustre coatings, polymer coatings, waxes, oils and other contaminations.

Product data	
Product code	IR
Packaging size	2.5 l
Viscosity at delivery	liquid
Shelf life - Original batch unopened	at least 2 years

Processing

Cleaning of waxed/oiled floors: Apply the product undiluted and let it act on the floor. Carefully clean the floor with brush, cleaning pad or cleaning machine with hard bristles. Never let the product dry on the floor. Immediately remove any dissolved dirt and rinse with clear water. Large areas shall be cleaned section by section. In the case of sensitive surfaces such as linoleum or in the case of stained surfaces, the product can be applied diluted with up to five parts of tap water. One litre is sufficient to treat up to 10 sqm. After this basic cleaning, oiled, waxed and stained surfaces must be treated again. For doing so, use our numerous Naturtrend products.

Cleaning of painting equipment and accessories: Use the product undiluted. Heavily soiled equipment (e.g., spray guns) can also be soaked directly in the immersion bath with IR. After the application thoroughly rinse the floor with water. In case of extremely persistent deposits of dirt, e.g., caused by paint or varnishes, we recommend using Universal Cleanser UR. Please see the Technical Data Sheet for this product.

Hardener - Thinner - Additives



tap water

up to 1:5 (IR/water), if required

Products from AkzoNobel Wood Coatings are exclusively produced for professional and industrial users, who have a basic knowledge of the handling and application of chemical/technical products for surface design. The processing instructions for reaching the qualities given in the leaflets should be regarded as non-binding recommendations and do not constitute any warranty. These recommendations are based on our experiences, including test series, and should facilitate and promote the work of our clients. Any potential deviation from ideal working conditions is within the responsibility of our clients and may affect the (end) result of the application. The purchaser is not relieved from his duties to inspect the product and its suitability for the surface to be processed, preferably trough trial processing. If in any doubt as to the handling or processing of the purchased product, our material experts as well as our application and laboratory technicians will help you to the best of their ability. AkzoNobel, of course, guarantees an impeccable quality of its products in the product specifications, yet the use thereof lies entirely within the responsibility of the purchaser. As long as we have not guaranteed – in writing – the specific characteristics and suitability of a product for a contractually agreed purpose, any advice or information given regarding the application or handling, even if the advice or information is given to the best of our knowledge, will not be binding nor will it constitute a warranty. AkzoNobel's liability for the use of its products by its customers is limited in its General Sales and Delivery Conditions, to which the purchaser is hereby referred. The applicable version of the Technical Data Sheet for this product can be downloaded from our websites. Previous versions of the Technical Data Sheets are rendered void with the issue of a new one. Date of issue: 2021-07-08 / 7