# Intensiv Cleanser IR





**Product description** 

Description Waterborne cleaning agent. Can be applied diluted and undiluted.

## **Range of application**

Description Descri

Product data	
Product code	IR
Packaging size	2.5 l
Viscosity at delivery	liquid
Shelf life - Original batch unopened	at least 1 year

### Processing

Cleaning of waxed/oiled floors: Apply the product undiluted and let it act on the floor. Carefully clean the floor with brush, cleaning pad or cleaning machine with hard bristles. Never let the product dry on the floor. Immediately remove any dissolved dirt and rinse with clear water. Large areas shall be cleaned section by section. In the case of sensitive surfaces such as linoleum or in the case of stained surfaces, the product can be applied diluted with up to five parts of tap water. One litre is sufficient to treat up to 10 sqm. After this basic cleaning, oiled, waxed and stained surfaces must be treated again. For doing so, use our numerous Naturtrend products.

Cleaning of painting equipment and accessories: Use the product undiluted. Heavily soiled equipment (e.g., spray guns) can also be soaked directly in the immersion bath with IR. After the application thoroughly rinse the floor with water. In case of extremely persistent deposits of dirt, e.g., caused by paint or varnishes, we recommend using Universal Cleanser UR. Please see the Technical Data Sheet for this product.

#### **Hardener - Thinner - Additives**



tap water up to 1:5 (IR/water), if required

Products from AkzoNobel Wood Coatings are exclusively produced for professional and industrial users, who have a basic knowledge of the handling and application of chemical/technical products for surface design. The processing instructions for reaching the qualities given in the leaflets should be regarded as non-binding recommendations and do not constitute any warranty. These recommendations are based on our experiences, including test series, and should facilitate and promote the work of our clients. Any potential deviation from ideal working conditions is within the responsibility of our clients and may affect the (end) result of the application. The purchaser is not relieved from his duties to inspect the product and its suitability for the surface to be processed, preferably trough trial processing. If in any doubt as to the handling or processing of the purchased product, our material experts as well as our application and laboratory technicians will help you to the best of their ability. AkzoNobel, of course, guarantees an impeccable quality of its products in its product for a contractually agreed purpose, any advice or information given regarding the application or handling, even if the advice or information is given to the best of suitability of the purchaser is limited in its General Sales and Delivery Conditions, to which the purchaser is hereby referred. The applicable version of the Technical Data Sheet for this product save bar downloaded from our websites. Previous versions of the Technical Data Sheet save nadered void with the issue of a new one. Date of issue: 2024-06-28 / 8

#### EMEA HQ

Akzo Nobel Hilden GmbH • Düsseldorfer Str. 96 - 100 • 40721 Hilden • Germany • www.akzonobel.com/wood