Correct Paintbox CTK



Product description

Description Correct Paintbox CTK with 24 universal, solvent-borne retouching inks.

Range of application

Description	Ideally suited for retouching smaller defects. Suitable for wooden surfaces, plastic surfaces (laminatos, flat laminatos, otc.)
	(laminates, flat laminates, etc.)

Product data		
Product	СТК	

code	
Packaging	1 paintbox consisting of: 24 ink pans 2 flasks
size	of solvent 2 red marten brushes

Preparation of substrates

Clean the spot to be treated. The substrate must be free from grease and dust and must be dry.

Processing



Slightly dissolve the paints with the red marten brush and the enclosed cellulose thinner. All colours can be mixed with each other. Apply thinly and repair the defects.

Drying time @ 20°C		
Dust dry	at least 3 minutes	
Overcoatable (aerosol can/spray gun)	at least 15 minutes	

Aftertreatment

The repaired spot can be overpainted with all Zweihorn® varnishes. When working on site, the varnish protection can be applied with a refillable Preval Sprayer or with Crystallit in the two-pack PUR aerosol can 5085.

Products from AkzoNobel Wood Coatings are exclusively produced for professional and industrial users, who have a basic knowledge of the handling and application of chemical/technical products for surface design. The processing instructions for reaching the qualities given in the leaflets should be regarded as non-binding recommendations and do not constitute any warranty. These recommendations are based on our experiences, including test series, and should facilitate and promote the work of our clients. Any potential deviation from ideal working conditions is within the responsibility of our clients and may affect the (end) result of the application. The purchaser is not relieved from his duties to inspect the product and its suitability for the surface to be processed, preferably trough trial processing. If in any doubt as to the handling or processing of the purchased product, our material experts as well as our application and laboratory technicians will help you to the best of their ability. AkzoNobel, of course, guarantees an impeccable quality of its products and its suitability of a contractually agreed purpose, any advice or information given regarding the application or handling, even if the advice or information is given to the best of our knowledge, will not be binding nor will it constitute a warranty. AkzoNobel's liability for the use of its products by its customers is limited in its General Sales and Delivery Conditions, to which the purchaser is hereby referred. The applicable version of the Technical Data Sheet for this product can be downloaded from our websites. Previous versions of the Technical Data Sheet for this product can be downloaded from our websites. Previous versions of the Technical Data Sheet for this product can be downloaded from our websites. Previous versions of the Technical Data Sheet for this product can be downloaded from our websites. Previous versions of the Technical Data Sheet for this product can be downloaded from our websites. Previous versions of the Technical Dat

EMEA HQ

Akzo Nobel Hilden GmbH ● Düsseldorfer Str. 96 - 100 ● 40721 Hilden ● Germany ● www.akzonobel.com/wood



AkzoNobel