HARMONIZING STAIN BASE



TÉCNOLOGIA

Base Solvente

TIPO DE PRODUCTO

Teñir

DENSIDAD (PESO ESPECÍFICO)

0,99 +/- 1%

VISSCOSIDAD DE ENTREGA

15 ± 2 Viscosidad en la entrega DIN 4 mm (seg.)

DESCRIPCIÓN DEL PRODUCTO

La Harmonizing Stain Base mezclada con las Antique Effect Patinas dará lugar a diferentes colores. Tinte semitransparente con una excelente resistencia a la luz. Asociado con diferentes diluyentes y ligantes, este tinte puede armonizarse.

- Marcado de poros cuando se mezcla con Harmonizing Wiping Stain
- Cubra con un acabado transparente base disolvente/agua





COLOR

Transparente

VIDA ÚTIL

12 moses

CONDICIONES DE ALMACENAJE

Mantener las latas bien cerradas, en un lugar bien ventilado, con temperatura controlada entre 10 y 30°C

CONTENIDO SOLIDO

14% ± 1%

Products from AkzoNobel Wood Coatings are exclusively produced for professional and industrial users, who have a basic knowledge of the handling and application of chemical/technical products from surface design. The processing instructions for reaching the qualities given in the leaflets should be regarded as non-binding recommendations and do not constitute any warranty. These recommendations are based on our experiences, including test series, and should facilitate and promote the work of our clients. Any potential deviation from ideal working conditions is within the responsibility of our clients and may affect the (end) result of the application. The purchaser is not relieved from his duties to inspect the product and its suitability for the surface to be processed, preferably trough trial processing. If in any doubt as to the handling or processing of the purchased product, our material experts as well as our application and laboratory technicians will help you to the best of their ability.

AkzoNobel, of course, guarantees an impeccable quality of its products in its product specifications, yet the use thereof lies entirely within the responsibility of the purchaser. As long as we have not guaranteed – in writing – the specific characteristics and suitability of a product for a contractually agreed purpose, any advice or information given regarding the application or handling, even if the advice or information is given to the best of our knowledge, will not be binding nor will it constitute a warranty. AkzoNobel's liability for the use of its products by its customers is limited in its

General Sales and Delivery Conditions, to which the purchaser is hereby referred. The applicable version of the Technical Data Sheet for this product can be downloaded from our websites. Previous versions of the Technical Data Sheets are rendered void with the issue of a new one. Date of issue: 2023-01-09 / 1

Akzo Nobel Hilden GmbH, Düsseldorfer Str. 96 - 100, 40721 Hilden, Germany www.sikkens-wood-coatings.com