




Antique-Finish Stain

S-9800-2733-COLOURLESS S-9800-COLOUR



| Product description | | Application | | |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|------|
| Description | Ready-to-use pigmented, solvent-based stain. With rustic pore-emphasizing on coarse-pored wood because of the black pigment. Also suitable for patinating. | Spray pressure (bar) | 1,0 - 1,5 | |
| | | Nozzle size (mm) | 0.8-1.3 | |
| | | Coverage (m²/l) | 7-12 | 7-15 |
| Range of application | | Drying time @ 20°C | | |
| Description | Many types of coarse-pored wood for rustic pore-emphasized staining appearance. Particularly suitable for oak, ash, mahogany and walnut. Very well suitable for patinating already varnished surfaces. | Overcoatable | at least 2 hours | |
| Product data | | Drying time | | |
| Product code | S-9800-2733-COLOURLESS S-9800-COLOUR | Drying can be optimized through air movement and temperature increase. | | |
| Packaging size | 1 l 5l 25l | Aftertreatment | | |
| Viscosity at delivery DIN 4 mm (sec.) | 10 ± 2 | The product can be overpainted with any Zweihorn® varnishes. Never apply solvent-based varnishes by rolling or brushing as the stain could be blurred by doing so. Coating with Naturtrend products is also possible. When doing so, product-related changes in colour must be taken into account. | | |
| Shelf life – Original container unopened | at least 2 years | | | |
| Gloss levels | | | | |
| Product number | | | | |
| S-9800-2733-COLOURLESS | | | | |
| Preparation of substrates | | | | |
|  | Graduated sanding of wood Carefully remove the sanding dust. Coarse-pore wood must be brushed out. | P120, P150, P180 | | |
| Processing | | | | |
|   | Shake or stir well before use! | | | |
| Brightening/Tinting | | | | |
| Brightening with product | Brightening with any quantity of Antique-Finish Stain colourless S 9800/2733. All stains can be mixed with each other. Subtle nuances can be given with Colour Concentrate CK. | | | |

Products from AkzoNobel Wood Coatings are exclusively produced for professional and industrial users, who have a basic knowledge of the handling and application of chemical/technical products for surface design. The processing instructions for reaching the qualities given in the leaflets should be regarded as non-binding recommendations and do not constitute any warranty. These recommendations are based on our experiences, including test series, and should facilitate and promote the work of our clients. Any potential deviation from ideal working conditions is within the responsibility of our clients and may affect the (end) result of the application. The purchaser is not relieved from his duties to inspect the product and its suitability for the surface to be processed, preferably through trial processing. If in any doubt as to the handling or processing of the purchased product, our material experts as well as our application and laboratory technicians will help you to the best of their ability. AkzoNobel, of course, guarantees an impeccable quality of its products in its product specifications, yet the use thereof lies entirely within the responsibility of the purchaser. As long as we have not guaranteed – in writing – the specific characteristics and suitability of a product for a contractually agreed purpose, any advice or information given regarding the application or handling, even if the advice or information is given to the best of our knowledge, will not be binding nor will it constitute a warranty. AkzoNobel's liability for the use of its products by its customers is limited in its General Sales and Delivery Conditions, to which the purchaser is hereby referred. The applicable version of the Technical Data Sheet for this product can be downloaded from our websites. Previous versions of the Technical Data Sheets are rendered void with the issue of a new one. Date of issue: 2023-09-22 / 28