Flattening Concentrate MK





Product description

Description Additive for matting solvent-based Zweihorn® paints/varnishes.

Range of application

Description	For matting of many solvent-based Zweihorn® paints and varnishes such as Wigranit® Novacolor, Diadur®, Crystallit®, Purolit, Super Duroffix. For the creation of crackle finish effects with Wigranit® Novacolor. See the description of effects on www.zweihorn.com.
-------------	---

Product data		
Product code	МК	
Packaging size	1	
Viscosity at delivery	liquid	
Shelf life - Original batch unopened	at least 2 years	

Gloss levels Example Crystallit® CL 7			
Dosage	Gloss level at 60°	Reduction of gloss level	
-	80%	-	
1%	60%	-20%	
3%	40%	-40%	
5%	25%	-55%	
7%	15%	-65%	
10%	8%	-72%	

Processing

Thoroughly shake before use and immediately add the product to the varnish.

Products from AkzoNobel Wood Coatings are exclusively produced for professional and industrial users, who have a basic knowledge of the handling and application of chemical/technical products for surface design. The processing instructions for reaching the qualities given in the leaflets should be regarded as non-binding recommendations and do not constitute any warranty. These recommendations are based on our experiences, including test series, and should facilitate and promote the work of our clients. Any potential deviation from ideal working conditions is within the responsibility of our clients and may affect the (end) result of the application. The purchaser is not relieved from his duties to inspect the product and its suitability for the surface to be processed, preferably trough trial processing. If in any doubt as to the handling or processing of the purchased product, our material experts as well as our application and laboratory technicians will help you to the best of their ability. AkzoNobel, of course, guarantees an impeccable quality of its products and its suitability of a contractually agreed purpose, any advice or information given regarding the application or handling, even if the advice or information is given to the best of four howledge, will not be binding nor will it constitute a warranty. AkzoNobel's liability for the use of its products by its customers is limited in its General Sales and Delivery Conditions, to which the purchaser is hereby referred. The applicable version of the Technical Data Sheet for this product can be downloaded from our websites. Previous versions of the Technical Data Sheet for this product can be downloaded from our websites. Previous versions of the Technical Data Sheet for this product can be downloaded from our websites. Previous versions of the Technical Data Sheets are rendered void with the issue of a new one. Date of issue: 2021-07-09 / 11

EMEA HQ

Akzo Nobel Hilden GmbH ● Düsseldorfer Str. 96 - 100 ● 40721 Hilden ● Germany ● www.akzonobel.com/wood