

AQUALIT COLOR P341

sikkens

WOOD COATINGS

INTERIOR

TÉCNOLOGIA

Base Agua

TIPO DE PRODUCTO

Primer

DESCRIPCIÓN DEL PRODUCTO

Imprimación base agua 1K y base neutra (BN00), utilizada para producir una imprimación de color personalizada y proporcionar una mejor capacidad de cubrimiento.



COLOR

Base Neutra BN00

18.4 KG

VIDA ÚTIL

12 meses

CONDICIONES DE ALMACENAJE

Entre 15 y 25°C en condiciones limpias y secas.

CONTENIDO SOLIDO

53,9% ± 1

DENSIDAD (PESO ESPECÍFICO)

1,30 +/- 1%

PREPARACIÓN DEL SUBSTRATO

	Superficies de madera en bruto. Lijado graduado de madera. Retire con cuidado el polvo de lijado. La madera de poro grueso debe cepillarse	P120, P150, P180
--	--	------------------------

DILUIR

agua del grifo

MÉTODO DE APLICACIÓN

Aplicación por pulverización airmix/airless, aplicación por pulverización de alta/baja presión

APLICACIÓN

Presión de pulverización (bar)	1.5 - 3.0	110 - 130
Tamaño de boquilla (mm)	2.0 - 2.5	0.33 - 0.38
Diluyente a añadir (%)	0 - 10	0 - 5
Viscosidad de aplicación DIN 4 mm (seg.)	100-140	120-140
Grosor de la Capa (g/m²)	100 - 120	100 - 120

TIEMPO DE SECADO @ 20°C

Lijable	Al menos 2 horas
Apilable	Al menos 2 horas

Products from AkzoNobel Wood Coatings are exclusively produced for professional and industrial users, who have a basic knowledge of the handling and application of chemical/technical products for surface design. The processing instructions for reaching the qualities given in the leaflets should be regarded as non-binding recommendations and do not constitute any warranty. These recommendations are based on our experiences, including test series, and should facilitate and promote the work of our clients. Any potential deviation from ideal working conditions is within the responsibility of our clients and may affect the (end) result of the application. The purchaser is not relieved from his duties to inspect the product and its suitability for the surface to be processed, preferably through trial processing. If in any doubt as to the handling or processing of the purchased product, our material experts as well as our application and laboratory technicians will help you to the best of their ability.

AkzoNobel, of course, guarantees an impeccable quality of its products in its product specifications, yet the use thereof lies entirely within the responsibility of the purchaser. As long as we have not guaranteed - in writing - the specific characteristics and suitability of a product for a contractually agreed purpose, any advice or information given regarding the application or handling, even if the advice or information is given to the best of our knowledge, will not be binding nor will it constitute a warranty. AkzoNobel's liability for the use of its products by its customers is limited in its

General Sales and Delivery Conditions, to which the purchaser is hereby referred. The applicable version of the Technical Data Sheet for this product can be downloaded from our websites. Previous versions of the Technical Data Sheets are rendered void with the issue of a new one. Date of issue: 2023-01-09 / 1