

# UV ADHESION SEALER WW 624 3500-001001

# AkzoNobel

<b>Type of Product</b> Waterborne UV Curing Transparent Sealer	<b>Application Viscosity</b> Ready for use, delivery viscosity
<b>Area of Use</b> Flooring	<b>Applied Amount</b> Approx. 6-12 g/m <sup>2</sup> dry film
<b>Packaging</b> 3500-001001-200 - 20 L	<b>Cleaning</b> Water/UV Cleaning 6800-001001 (62222)
<b>UV Curing Products</b> UV lacquers react when exposed to ultra-violet radiation, including sunlight.	<b>Empty Packaging</b> Disposal according to local regulations.
<b>Waterborne Products</b> Any part of the application equipment directly exposed to this product should be made of plastic or stainless steel.	<b>UV Curing</b> All water must be evaporated before UV curing. Cures by UV radiation only. Curing: 1 UV Hg Lamp(s) 80 W/cm @ 5 m/min.
<b>Binder</b> Acrylic	<b>Additional Drying Information</b> Please contact our Technical Staff for specific data concerning curing conditions on your line.
<b>Solid Contents</b> Approx. 57 % by weight	<b>HSE Information</b> Use safety gloves and safety eyewear/face shield during the work. See Safety Data Sheet for further information.
<b>Delivery Viscosity</b> Approx. 75-105 sec DIN Cup 4 @ 23 °C	
<b>Density</b> Approx. 1,09 kg/l	
<b>Thinner</b> Water	
<b>Shelf Life</b> 12 months in original, unopened package when stored following the storage conditions mentioned below. After the expiry date, contact our Technical Staff for an estimation of usability.	
<b>Storage Conditions</b> Between 15 and 25 °C under clean and dry conditions. Keep from freezing. Protect from direct sunlight.	
<b>Methods</b> Smooth roller coater	

Products from AkzoNobel Wood Coatings are exclusively produced for professional and industrial users, who have a basic knowledge of the handling and application of chemical/technical products for surface design. The processing instructions for reaching the qualities given in the leaflets should be regarded as non-binding recommendations and do not constitute any warranty. These recommendations are based on our experiences, including test series, and should facilitate and promote the work of our clients. Any potential deviation from ideal working conditions is within the responsibility of our clients and may affect the (end) result of the application. The purchaser is not relieved from his duties to inspect the product and its suitability for the surface to be processed, preferably through trial processing. If in any doubt as to the handling or processing of the purchased product, our material experts as well as our application and laboratory technicians will help you to the best of their ability. AkzoNobel, of course, guarantees an impeccable quality of its products in its product specifications, yet the use thereof lies entirely within the responsibility of the purchaser. As long as we have not guaranteed – in writing – the specific characteristics and suitability of a product for a contractually agreed purpose, any advice or information given regarding the application or handling, even if the advice or information is given to the best of our knowledge, will not be binding nor will it constitute a warranty. AkzoNobel's liability for the use of its products by its customers is limited in its General Sales and Delivery Conditions, to which the purchaser is hereby referred. The applicable version of the Technical Data Sheet for this product can be downloaded from our websites. Previous versions of the Technical Data Sheets are rendered void with the issue of a new one. Date of issue: 2024-01-31 / 3

EMEA HQ  
 Akzo Nobel Industrial Coatings AB SE-205 17 Malmö Tel. +46 40 35 50 00 Fax +46 40 35 51 32 www.akzonobel.com/wood

# AkzoNobel