# **High-Gloss Anti-Haze** HAS





#### **Product description** Waterborne high-gloss polish with very fine grain to remove residues of the grinding and Description polishing pastes HSP and HPP and any hazes on high-gloss surfaces.

#### **Range of application** High-Gloss Anti-Haze HAS completes the polishing procedure with fines grain and removes the last haze on any high-gloss Description furniture surfaces. Also perfectly suited for mechanical or manual refreshing or restoring of the original shine of high-gloss surfaces.

Product data	
Product code	HAS
Packaging size	1 kg
Viscosity at delivery	pasty
Shelf life - Original batch unopened	at least 2 years

## **Preparation of substrates**

Polish the surfaces as described in the Technical Data Sheets of the products High-Gloss Grinding Paste HSP and High-Gloss Polishing Paste HPP.

#### Processing

High-Gloss Anti-Haze HAS should be applied with a rotating polishing machine with a lambskin. First, apply the paste onto the lambskin and manually distribute it on the surface without polishing. Then start the polishing process at lowest speed and slowly increase the speed. The polishing machine is passed over the surface with low pressure while moving constantly, so that the surface does not become too hot. The surface can also be cooled during polishing by means of a water sprayer. High-Gloss Anti- Haze HAS can be applied on the surface several times until the result is satisfactory. On dark surfaces, the product can be finally applied with a smooth polishing pad or a waffle pad. High-Gloss Anti-Haze HAS can also be applied manually with a clean, lint-free and soft cloth. This is particularly recommended for refreshing or restoring the shine of stationary objects. A small amount of High- Gloss Anti-Haze HAS is applied on the high-gloss surface by means of a cloth and circular motion until the entire surface is shiny and until all product residues have been removed.

## **Hardener - Thinner - Additives**



spray on the surface, if required

## Aftertreatment

If the polishing result is satisfactory, the surface can be rubbed with Polishing Water S68. By doing so, an extremely thin silicone-containing protective film is applied. The surfaces will then be more scratch resistant and get a cosy surface smoothness. Please see the Technical Data Sheet for this product.

Products from AkzoNobel Wood Coatings are exclusively produced for professional and industrial users, who have a basic knowledge of the handling and application of chemical/technical products for surface design. The processing instructions for reaching the qualities given in the leaflets should be regarded as non-binding recommendations and do not constitute any warranty. These recommendations are based on our experiences, including test series, and should facilitate and promote the work of our clients. Any potential deviation from ideal working conditions is within the responsibility of our clients and may affect the (end) result of the application. The purchaser is not relieved from his duties to inspect the product and its suitability for the surface to be processed, preferably trough trial processing. If in any doubt as to the handling or processing of the purchased product, our material experts as well as our application and laboratory technicians will help you to the best of their ability. AkzoNobel, of course, guarantees an impeccable quality of its products in the responsibility of the application and pay on quaranteed as were not quaranteed as the specific characteristics and Its product specifications, yet the use thereof lies entirely within the responsibility of the purchaser. As long as we have not guaranteed – in writing – the specific characteristics and suitability of a product for a contractually agreed purpose, any advice or information given regarding the application or handling, even if the advice or information is given to the best of our knowledge, will not be binding nor will it constitute a warranty. AkzoNobel's liability for the use of its products by its customers is limited in its General Sales and Delivery Conditions, to which the purchaser is hereby referred. The applicable version of the Technical Data Sheet for this product can be downloaded from our websites. Previous versions of the Technical Data Sheets are rendered void with the issue of a new one. Date of issue: 2021-07-08 / 9

AkzoNobel

EMEA HQ