

Procryl Parquet Cleanser PPR




Product description	
Description	Concentrate for the cleaning of varnished wooden floors and laminate floors.

Range of application	
Description	As universal and gentle care and cleaning of all varnished wooden floors, laminate floors as well as clinker or stone floors.

Product data	
Product code	PPR
Packaging size	1 l
Viscosity at delivery	liquid
Shelf life – Original container unopened	at least 1 year

Mixture	
Normal soiling Yield (1 litre concentrate)	200 ml into 10 litres of water 5 l
Heavy soiling Yield (1 litre concentrate)	500 ml into 10 litres of water 2 l

Preparation of substrates
First thoroughly remove dirt from the floor by means of vacuuming.

Processing
 <p>Add the indicated quantity of the concentrate into the mopping water and clean the floor with a slightly damp cloth. We recommend working with two buckets. One for the clean cleaning solution and the other one for the waste water. Do not use clear water to wipe again after cleaning. The product can also be used in cleaning machines.</p>

Aftertreatment
Depending on the visual appearance of the floor, care treatment with Procryl Parquet Care PPP can be carried out after the cleaning procedure.

Products from AkzoNobel Wood Coatings are exclusively produced for professional and industrial users, who have a basic knowledge of the handling and application of chemical/technical products for surface design. The processing instructions for reaching the qualities given in the leaflets should be regarded as non-binding recommendations and do not constitute any warranty. These recommendations are based on our experiences, including test series, and should facilitate and promote the work of our clients. Any potential deviation from ideal working conditions is within the responsibility of our clients and may affect the (end) result of the application. The purchaser is not relieved from his duties to inspect the product and its suitability for the surface to be processed, preferably through trial processing. If in any doubt as to the handling or processing of the purchased product, our material experts as well as our application and laboratory technicians will help you to the best of their ability. AkzoNobel, of course, guarantees an impeccable quality of its products in its product specifications, yet the use thereof lies entirely within the responsibility of the purchaser. As long as we have not guaranteed – in writing – the specific characteristics and suitability of a product for a contractually agreed purpose, any advice or information given regarding the application or handling, even if the advice or information is given to the best of our knowledge, will not be binding nor will it constitute a warranty. AkzoNobel's liability for the use of its products by its customers is limited in its General Sales and Delivery Conditions, to which the purchaser is hereby referred. The applicable version of the Technical Data Sheet for this product can be downloaded from our websites. Previous versions of the Technical Data Sheets are rendered void with the issue of a new one. Date of issue: 2024-06-28 / 10