

TECHNOLOGIA

Wodnorozcieńczalny

RODZAJ PRODUKTU

Lakier nawierzchniowy

OPIS PRODUKTU

Światłotrwwały wszechstronny jedno- lub dwuskładnikowy lakier nawierzchniowy na schodyz dobrą odpornością mechaniczną i chemiczną jako jednoskładnikowy, układ dwuskładnikowy poprawi skuteczność.

- Dobra przejrzystość i właściwości wypełniające
- Dobra odporność mechaniczna i chemiczna (szczególnie na kremy i smary)
- Może być użyty jako jednoskładnikowy lub dwuskładnikowy (układ dwuskładnikowy poprawi skuteczność)
- Odporność na skrzywienie tylko jako jednoskładnikowy
- Łatwy do szlifowania



KOLOR

Bezbarwny

POZIOM POŁYSKU (OK.GU @ 60°)

10

5 L

OKRES PRZECHOWYWANIA

12 miesięcy

WARUNKI PRZECHOWYWANIA

Trzymać puszkę szczelnie zamkniętą, w dobrze wentylowanym pomieszczeniu z kontrolą temperatury pomiędzy 10 a 30°C

ZAWARTOŚĆ CIAŁ STAŁYCH

29.7% ± 1%

GĘSTOŚĆ (CIĘŻAR WŁAŚCIWY)

1,03 +/- 1%

LEPKOŚĆ HANDLOWA

60 ± 5 lepkość handlowa DIN 4 mm

PRZYGOTOWANIE SUBSTRATÓW

	Powierzchnie z surowego drewna. Stopniowane szlifowanie drewna. Dokładnie usunąć pył po szlifowaniu. Drewno otwartoporowe należy wyszczotkować.	P120, P150, P180
	Drewno egzotyczne / drewno bogate w ekstrakty lub gdy potrzeba mocniej uwidocznić rysunek drewna	Zaizolować przy użyciu AIS180.
	Powierzchnie pokryte pigmentowanym lakierem nawierzchniowym AQUALIT COLOR	Lakier nawierzchniowy musi być nałożony bez szlifowania międzyoperacyjnego po 6 do maksymalnie 24 godzinach.

UTWARDZACZ (WAGOWO)

HWA 6000	5%	do 4 godzin	Utwardzanie opcjonalne
----------	----	-------------	------------------------

ROZCIĘNCZANIE

TWA 9000-F lub woda kranowa

METODA APLIKACJI

Aplikacja natryskiem i pędzlem

Products from AkzoNobel Wood Coatings are exclusively produced for professional and industrial users, who have a basic knowledge of the handling and application of chemical/technical products for surface design. The processing instructions for reaching the qualities given in the leaflets should be regarded as non-binding recommendations and do not constitute any warranty. These recommendations are based on our experiences, including test series, and should facilitate and promote the work of our clients. Any potential deviation from ideal working conditions is within the responsibility of our clients and may affect the (end) result of the application. The purchaser is not relieved from his duties to inspect the product and its suitability for the surface to be processed, preferably through trial processing. If in any doubt as to the handling or processing of the purchased product, our material experts as well as our application and laboratory technicians will help you to the best of their ability.

AkzoNobel, of course, guarantees an impeccable quality of its products in its product specifications, yet the use thereof lies entirely within the responsibility of the purchaser. As long as we have not guaranteed – in writing – the specific characteristics and suitability of a product for a contractually agreed purpose, any advice or information given regarding the application or handling, even if the advice or information is given to the best of our knowledge, will not be binding nor will it constitute a warranty. AkzoNobel's liability for the use of its products by its customers is limited in its

General Sales and Delivery Conditions, to which the purchaser is hereby referred. The applicable version of the Technical Data Sheet for this product can be downloaded from our websites. Previous versions of the Technical Data Sheets are rendered void with the issue of a new one. Date of issue: 2023-01-09 / 1

APLIKACJA

			
Ciśnienie natrysku (bar)	1.5 - 2.0	80 - 100	
Rozmiar dyszy (mm)	1.8-2.0	0.23 - 0.28	
Dodatek rozcieńczalnika (%)	0 - 10	0 - 10	0 - 10
Lepkość robocza DIN 4 (s)	40-50	40-50	40 - 50
Grubość warstwy (g/m²)	100 - 120	100 - 120	100 - 120

CZAS SCHNIĘCIA @ 20°C

Pyłosuchy	Przynajmniej 40 minut
Suchy w dotyku	Przynajmniej 90 minut
Szlifowalny	Przynajmniej 4 godziny
Gotowy do transportu	Przynajmniej 12 godzin

Products from AkzoNobel Wood Coatings are exclusively produced for professional and industrial users, who have a basic knowledge of the handling and application of chemical/technical products for surface design. The processing instructions for reaching the qualities given in the leaflets should be regarded as non-binding recommendations and do not constitute any warranty. These recommendations are based on our experiences, including test series, and should facilitate and promote the work of our clients. Any potential deviation from ideal working conditions is within the responsibility of our clients and may affect the (end) result of the application. The purchaser is not relieved from his duties to inspect the product and its suitability for the surface to be processed, preferably through trial processing. If in any doubt as to the handling or processing of the purchased product, our material experts as well as our application and laboratory technicians will help you to the best of their ability.

AkzoNobel, of course, guarantees an impeccable quality of its products in its product specifications, yet the use thereof lies entirely within the responsibility of the purchaser. As long as we have not guaranteed – in writing – the specific characteristics and suitability of a product for a contractually agreed purpose, any advice or information given regarding the application or handling, even if the advice or information is given to the best of our knowledge, will not be binding nor will it constitute a warranty. AkzoNobel's liability for the use of its products by its customers is limited in its

General Sales and Delivery Conditions, to which the purchaser is hereby referred. The applicable version of the Technical Data Sheet for this product can be downloaded from our websites. Previous versions of the Technical Data Sheets are rendered void with the issue of a new one. Date of issue: 2023-01-09 / 1