

TECHNOLOGY

Waterborne

PRODUCT TYPE

Additive

APPLICATION METHOD

Stir in thoroughly! Add the product instead of tap water in the quantity recommended for the respective product. By doing so, the way of processing of the products is not changed. Please see the separate Technical Data Sheets for these products.

PRODUCT DESCRIPTION

Thinner with an integrated surface-active additive to be used in waterborne Sikkens® paint and varnish systems. The product is used to adjust the viscosity of the paint and, at the same time, to accelerate drying. Especially in the area of edges and profiles, film formation is optimized so that a loss of edge covering in these areas is reduced or even prevented. By adding the product, wetting of the substrate of wood and wooden materials is also improved. The product can be added to many waterborne fillers, paints and varnishes made by Sikkens® instead of tap water.



PACK SIZES

5261316 - 1 L

SHELF LIFE

12 months in original, unopened package

STORAGE CONDITIONS

Between 15 and 25°C under clean and dry conditions.

DENSITY (SPECIFIC WEIGHT)

0,98 +/- 1%

DELIVER VISCOSITY

Liquid

Products from AkzoNobel Wood Coatings are exclusively produced for professional and industrial users, who have a basic knowledge of the handling and application of chemical/technical products for surface design. The processing instructions for reaching the qualities given in the leaflets should be regarded as non-binding recommendations and do not constitute any warranty. These recommendations are based on our experiences, including test series, and should facilitate and promote the work of our clients. Any potential deviation from ideal working conditions is within the responsibility of our clients and may affect the (end) result of the application. The purchaser is not relieved from his duties to inspect the product and its suitability for the surface to be processed, preferably through trial processing. If in any doubt as to the handling or processing of the purchased product, our material experts as well as our application and laboratory technicians will help you to the best of their ability.

AkzoNobel, of course, guarantees an impeccable quality of its products in its product specifications, yet the use thereof lies entirely within the responsibility of the purchaser. As long as we have not guaranteed - in writing - the specific characteristics and suitability of a product for a contractually agreed purpose, any advice or information given regarding the application or handling, even if the advice or information is given to the best of our knowledge, will not be binding nor will it constitute a warranty. AkzoNobel's liability for the use of its products by its customers is limited in its

General Sales and Delivery Conditions, to which the purchaser is hereby referred. The applicable version of the Technical Data Sheet for this product can be downloaded from our websites. Previous versions of the Technical Data Sheets are rendered void with the issue of a new one. Date of issue: 2025-12-15 / 6