

WV 805

8520-000671-000

sikkens
WOOD COATINGS



Product description

Maintenance cloth for refreshing and protecting weathered painted surfaces of entry doors. Regular use extend the maintenance periods. - water and dirt resistant - good weather resistance - good colour and gloss refresher

Colour

Colourless

Processing

The surface to be treated should first of all be cleaned thoroughly with the Special Cleaner* or suitable household cleaning agents and allowed to fully dry. After drying, the cleaned surface should be gently and evenly wiped using the maintenance cloth moistened with the balm. The cloth should be folded into a usable shape and the face of the cloth changed regularly during the application process.

Application temperature

+5 - 30 °C for substrate, air and material at approx. 60 % R.H.

Drying

After the application, a drying time of approx. 30 min should be allowed.

Storage

Minimum storage stability at room temperature: 2 years
Store in a cool but frost-free place.

Disposal

The maintenance cloth can be disposed after use in the general waste disposal.

Safety Data Sheet

Further data in the Material Safety Data Sheet according to 91/155/EEC www.sikkens-wood-coatings.com
Downloads Safety Data Sheets

Warning

Before use, read the identification and product information. Always follow customary protection measures, even when working with low emission products.

VOC Directive

Not subject to marking.

General instructions

Through the application of maintenance milk, painted surfaces obtain the original freshness. With regular use (1-2 yearly in spring and autumn), the durability of the coating system rises and maintenance periods can be extended. Defect coating systems cannot be repaired with maintenance milk. The correct products are referred to on the technical data sheets.

Notes

Do not use on hot surfaces or direct sun radiation. Before reworking of the maintained paint surface, the surface has to be cleaned with white spirit followed with a sanding (sanding paper K240). The clean and dry surface can be repainted with the Sikkens maintenance products.

Products from AkzoNobel Wood Coatings are exclusively produced for professional and industrial users, who have a basic knowledge of the handling and application of chemical/technical products for surface design. The processing instructions for reaching the qualities given in the leaflets should be regarded as non-binding recommendations and do not constitute any warranty. These recommendations are based on our experiences, including test series, and should facilitate and promote the work of our clients. Any potential deviation from ideal working conditions is within the responsibility of our clients and may affect the (end) result of the application. The purchaser is not relieved from his duties to inspect the product and its suitability for the surface to be processed, preferably through trial processing. If in any doubt as to the handling or processing of the purchased product, our material experts as well as our application and laboratory technicians will help you to the best of their ability. AkzoNobel, of course, guarantees an impeccable quality of its products in its product specifications, yet the use thereof lies entirely within the responsibility of the purchaser. As long as we have not guaranteed - in writing - the specific characteristics and suitability of a product for a contractually agreed purpose, any advice or information given regarding the application or handling, even if the advice or information is given to the best of our knowledge, will not be binding nor will it constitute a warranty. AkzoNobel's liability for the use of its products by its customers is limited in its General Sales and Delivery Conditions, to which the purchaser is hereby referred. The applicable version of the Technical Data Sheet for this product can be downloaded from our websites. Previous versions of the Technical Data Sheets are rendered void with the issue of a new one. Date of issue: 2020-05-29 / 6

EMEA HQ
Akzo Nobel Hilden GmbH ● Düsseldorf Str. 96 - 100 ● 40721 Hilden ● Germany ● www.akzonobel.com/wood

AN_204450_060919

1/1

AkzoNobel

AN_20450_060919