

WV 887

8558-003001-050

sikkens
WOOD COATINGS



Product description

Defoamer for waterborne products. To reduce the formation of foam during application. Suitable for CETOL WF 98xx and RUBBOL WF 33XX ranges.

Colour

Colourless to light yellowish

Density (specific weight)

approx. 1.00 - 1.03 kg/l

Packaging

8558-003001-050 - 5 L

Processing

For a better distribution of the defoamer it is recommended to pour the quantity of defoamer into a partial amount of the original material and mix before returning mixture into the complete amount and thoroughly stirring. Do not premix with water.

Consumption

Amount to be added: 0.1 - 0.5%

Storage

The minimum shelf life in the unopened original container is two years; Storage temperature +5 - +30 ° C. After expiry of the BBD, the product may still be processable, but the product properties may differ from "fresh" material. For that reason, the user must apply expired material with particular attention. Started containers must be closed carefully! Store in a cool but frost-free place.

Disposal

Only empty containers may be recycled. Dispose of material residues according to local regulations. The EC waste code applicable to such material is: 08 01 12

Safety Data Sheet

Further data in the Material Safety Data Sheet according to 91/155/EEC www.sikkens-wood-coatings.com
Downloads Safety Data Sheets

Warning

Before use, read the identification and product information. Always follow customary protection measures, even when working with low emission products.

VOC Directive

Not subject to marking.

General instructions

For use in technical industrial companies and intended only for recommended Sikkens systems.

Notes

The coating system mentioned here is exemplary, other systems are possible. All external materials coming into contact with the coating system (e.g. filler, adhesive tapes, sealants, cleaners, etc.) must be tested for compatibility by the user. Please refer to the relevant Technical Data Sheets and ask your Sikkens Sales Representative or at the factory for a system consultation.

Products from AkzoNobel Wood Coatings are exclusively produced for professional and industrial users, who have a basic knowledge of the handling and application of chemical/technical products for surface design. The processing instructions for reaching the qualities given in the leaflets should be regarded as non-binding recommendations and do not constitute any warranty. These recommendations are based on our experiences, including test series, and should facilitate and promote the work of our clients. Any potential deviation from ideal working conditions is within the responsibility of our clients and may affect the (end) result of the application. The purchaser is not relieved from his duties to inspect the product and its suitability for the surface to be processed, preferably through trial processing. If in any doubt as to the handling or processing of the purchased product, our material experts as well as our application and laboratory technicians will help you to the best of their ability. AkzoNobel, of course, guarantees an impeccable quality of its products in its product specifications, yet the use thereof lies entirely within the responsibility of the purchaser. As long as we have not guaranteed – in writing – the specific characteristics and suitability of a product for a contractually agreed purpose, any advice or information given regarding the application or handling, even if the advice or information is given to the best of our knowledge, will not be binding nor will it constitute a warranty. AkzoNobel's liability for the use of its products by its customers is limited in its General Sales and Delivery Conditions, to which the purchaser is hereby referred. The applicable version of the Technical Data Sheet for this product can be downloaded from our websites. Previous versions of the Technical Data Sheets are rendered void with the issue of a new one. Date of issue: 2023-05-02 / 12

EMEA HQ

Akzo Nobel Hilden GmbH ● Düsseldorf Str. 96 - 100 ● 40721 Hilden ● Germany ● www.akzonobel.com/wood

AN_204450_060919

1/1

AkzoNobel

AN_20450_060919