





Product description	
Description	Care product for the refreshment of varnished wooden floors.

Range of application	
Description	For the care and refreshment of all varnished wooden floors and laminate floors.

Product data	
Product code	PPP
Packaging size	1 l
Viscosity at delivery	liquid
Shelf life - Original container unopened	at least 1 year

Preparation of substrates	
	The first care of varnished wooden floors must be done after 7 days at the earliest. First thoroughly remove dirt from the floor by means of vacuuming. In case the floor should be extremely dirty, it must first be cleaned with Procryl Parquet Cleanser PPR.

Processing	
	The product is ready for use. The floor is evenly treated with a slightly damp lint-free cloth. After a drying time of approx. 30 minutes, the floor is ready. Subsequent polishing is not required.

Aftertreatment	
Depending on the usage of the floor, care can be carried out every 2 - 3 months after appropriate previous cleaning.	

Products from AkzoNobel Wood Coatings are exclusively produced for professional and industrial users, who have a basic knowledge of the handling and application of chemical/technical products for surface design. The processing instructions for reaching the qualities given in the leaflets should be regarded as non-binding recommendations and do not constitute any warranty. These recommendations are based on our experiences, including test series, and should facilitate and promote the work of our clients. Any potential deviation from ideal working conditions is within the responsibility of our clients and may affect the (end) result of the application. The purchaser is not relieved from his duties to inspect the product and its suitability for the surface to be processed, preferably through trial processing. If in any doubt as to the handling or processing of the purchased product, our material experts as well as our application and laboratory technicians will help you to the best of their ability. AkzoNobel, of course, guarantees an impeccable quality of its products in its product specifications, yet the use thereof lies entirely within the responsibility of the purchaser. As long as we have not guaranteed - in writing - the specific characteristics and suitability of a product for a contractually agreed purpose, any advice or information given regarding the application or handling, even if the advice or information is given to the best of our knowledge, will not be binding nor will it constitute a warranty. AkzoNobel's liability for the use of its products by its customers is limited in its General Sales and Delivery Conditions, to which the purchaser is hereby referred. The applicable version of the Technical Data Sheet for this product can be downloaded from our websites. Previous versions of the Technical Data Sheets are rendered void with the issue of a new one. Date of issue: 2024-06-28 / 8