



Product description	
Description	For the preparation of waxed high-quality wood surfaces. With the pleasant scent of beeswax.
Range of application	
Description	Almost all wooden furniture in the interior. To refresh previously oiled surfaces or dulled coated surfaces. Perfect for slightly strained surfaces such as cabinets and profiles. Due to the pleasant scent perfect for the interior of cabinets.
Product data	
Product code	NBW
Packaging size	5l 750 ml
Viscosity at delivery	pasty
Shelf life – Original container unopened	at least 2 years
Preparation of substrates	
Raw wooden surfaces. Furniture	P180, P240, P320
wear-resistant surfaces of wooden furniture	First, treat with deeply penetrating Naturtrend oils.
Processing	
  	The product is applied by means of a brush (not too soft), a bale of cloth or by hot-spraying. (max. 35°C) The furniture surface is brushed to shine after the indicated drying time.
Application	
Coverage (m <sup>2</sup> /l)	15
Drying time @ 20°C	
Polishable	at least 3 hours
First, light load	at least 24 hours
Full strength, ready to walk on	at least 3 days
Aftertreatment	
After drying and previous sanding (furniture P320/P400, floors P240), the product can be applied again. Naturtrend surfaces must be given a follow-up treatment from time to time. Appropriate products can be found in the Cleaning & Care section. In case wear should be too heavy, complete rebuild might be useful.	
Special notes	
Tools should be cleaned with Naturtrend Furniture Cleanser NMR, Special Intensive Cleanser IR or white spirit.	
The product is biodegradable; however, it must not be drained into the sewage system. (Regional provisions must be followed!)	
The product can be processed with smooth transition, it is extremely heat resistant (up to 120° C), step proof and dirt resistant.	
For wooden surfaces treated with Naturtrend products it is not possible to indicate definitive drying times. Terms such as "dust dry" or "sandable" used for conventional systems cannot be transferred.	
Test standards	
DIN 68861/1C Chemical exposure of furniture surfaces	

Products from AkzoNobel Wood Coatings are exclusively produced for professional and industrial users, who have a basic knowledge of the handling and application of chemical/technical products for surface design. The processing instructions for reaching the qualities given in the leaflets should be regarded as non-binding recommendations and do not constitute any warranty. These recommendations are based on our experiences, including test series, and should facilitate and promote the work of our clients. Any potential deviation from ideal working conditions is within the responsibility of our clients and may affect the (end) result of the application. The purchaser is not relieved from his duties to inspect the product and its suitability for the surface to be processed, preferably through trial processing. If in any doubt as to the handling or processing of the purchased product, our material experts as well as our application and laboratory technicians will help you to the best of their ability. AkzoNobel, of course, guarantees an impeccable quality of its products in its product specifications, yet the use thereof lies entirely within the responsibility of the purchaser. As long as we have not guaranteed – in writing – the specific characteristics and suitability of a product for a contractually agreed purpose, any advice or information given regarding the application or handling, even if the advice or information is given to the best of our knowledge, will not be binding nor will it constitute a warranty. AkzoNobel's liability for the use of its products by its customers is limited in its General Sales and Delivery Conditions, to which the purchaser is hereby referred. The applicable version of the Technical Data Sheet for this product can be downloaded from our websites. Previous versions of the Technical Data Sheets are rendered void with the issue of a new one. Date of issue: 2024-08-26 / 15