




Aqua Creative Stain

ACB-200-COLOURLESS ACB-BLUE ACB-RAL-9005-BLACK ACB-RAL-9010-PURE-WHITE ACB-RED ACB-YELLOW



Product description	
Description	Ready-to-use, pigmented wood stain. Colour metrics stored so that a vast number of colour shades can be mixed. Opaque to transparent colours, e.g., according to Sikkens or RAL. Emphasized pores if applied by brush, flat pore if applied by spraying.
Range of application	
Description	Almost all types of wood in the interior.
Product data	
Product code	ACB-200-COLOURLESS ACB-RAL-9005-BLACK ACB-RAL-9010-PURE-WHITE ACB-RED ACB-BLUE ACB-YELLOW
Product color	colourless
Packaging size	1 l 5l
Viscosity at delivery DIN 4 mm (sec.)	12 sec. ± 2
Shelf life – Original container unopened	at least 1 year
Gloss levels	
Product number	
ACB-200-COLOURLESS	
ACB-RAL-9005-BLACK	
ACB-RAL-9010-PURE-WHITE	
ACB-RED	
ACB-YELLOW	
Preparation of substrates	
	Graduated sanding of wood Carefully remove the sanding dust. Coarse-pore wood must be brushed out.
P120, P150, P180	
Processing	
 	Shake or stir well before use! Always keep the product in motion during the application in order to avoid differences in colour.

Brightening/Tinting		
Brightening with product	Brightening with any quantity of Aqua Creative Stain colourless ACB/200. All stains can be mixed with each other. Nuances can be given with basic colours.	
Application		
Spray pressure (bar)	1.0-1.5	
Nozzle size (mm)	0.8-1.3	
Coverage (m²/l)	7-12	7-15
Drying time @ 20°C		
Overcoatable	at least 4 hours	
Drying time		
Drying can be optimized through air movement and temperature increase.		
Aftertreatment		
All Zweihorn® varnishes are suitable as top coat. For maximum colour stability we recommend using lightfast varnish systems such as Crystallit®, Variocryl®, etc. Coating with Naturtrend products is also possible. When doing so, product- related changes in colour must be taken into account.		

Products from AkzoNobel Wood Coatings are exclusively produced for professional and industrial users, who have a basic knowledge of the handling and application of chemical/technical products for surface design. The processing instructions for reaching the qualities given in the leaflets should be regarded as non-binding recommendations and do not constitute any warranty. These recommendations are based on our experiences, including test series, and should facilitate and promote the work of our clients. Any potential deviation from ideal working conditions is within the responsibility of our clients and may affect the (end) result of the application. The purchaser is not relieved from his duties to inspect the product and its suitability for the surface to be processed, preferably through trial processing. If in any doubt as to the handling or processing of the purchased product, our material experts as well as our application and laboratory technicians will help you to the best of their ability. AkzoNobel, of course, guarantees an impeccable quality of its products in its product specifications, yet the use thereof lies entirely within the responsibility of the purchaser. As long as we have not guaranteed – in writing – the specific characteristics and suitability of a product for a contractually agreed purpose, any advice or information given regarding the application or handling, even if the advice or information is given to the best of our knowledge, will not be binding nor will it constitute a warranty. AkzoNobel's liability for the use of its products by its customers is limited in its General Sales and Delivery Conditions, to which the purchaser is hereby referred. The applicable version of the Technical Data Sheet for this product can be downloaded from our websites. Previous versions of the Technical Data Sheets are rendered void with the issue of a new one. Date of issue: 2025-03-10 / 32