

<p><b>Type of Product</b></p> <p>Solventborne Pigment Paste</p>	<p><b>Empty Packaging</b></p> <p>Disposal according to local regulations.</p>
<p><b>Packaging</b></p> <p>8050-451009-010 - 1 L</p>	<p><b>Remarks</b></p> <p>Mixing instructions: the TI 711 colorants - colour formulation + binder SC91 is added into a small amount of Stain Thinner, directly in the delivery can. Shake the can well for at least 2-3 min. Then add to the can, the remaining amount of Stain Thinner to achieve final volume.</p>
<p><b>Notes</b></p> <p>Ti 711 is a mixture of a binder, organic solvents and micronized, transparent pigments. Ti711 is a light fast pigment colorant. Ti 711 consists of 8 colorants and one clear SB base. It is used in combination with Stain Thinner 260, 6500-026001 and are for application on wood indoors</p> <p>Suitable for tinting in some SB lacquers, (max. add. 5 w/w%) and intermixable to any shade. Please contact our Technical Staff.</p>	<p><b>HSE Information</b></p> <p>See Safety Data Sheet for further information.</p>
<p><b>Stains</b></p> <p>The stain cannot be used on its own, must always be overcoated. Do not sand the stain. Pigmented stains should be stirred or shake carefully before use.</p>	
<p><b>Pigment Concentrates</b></p> <p>Requires careful stirring or shaking before use.</p>	
<p><b>Solid Contents</b></p> <p>Approx. 30 % by weight</p>	
<p><b>Density</b></p> <p>Approx. 1,03 kg/l</p>	
<p><b>Shelf Life</b></p> <p>12 months in original, unopened package when stored following the storage conditions mentioned below. After the expiry date, contact our Technical Staff for an estimation of usability.</p>	
<p><b>Storage Conditions</b></p> <p>Between 15 and 25 °C under clean and dry conditions.</p>	
<p><b>Remarks</b></p> <p>When producing the solvent based stain, mix Ti711 with 6500-026001 + binder SC91. The final product is named TINTEX STAIN SST 711.</p>	

Products from AkzoNobel Wood Coatings are exclusively produced for professional and industrial users, who have a basic knowledge of the handling and application of chemical/technical products for surface design. The processing instructions for reaching the qualities given in the leaflets should be regarded as non-binding recommendations and do not constitute any warranty. These recommendations are based on our experiences, including test series, and should facilitate and promote the work of our clients. Any potential deviation from ideal working conditions is within the responsibility of our clients and may affect the (end) result of the application. The purchaser is not relieved from his duties to inspect the product and its suitability for the surface to be processed, preferably through trial processing. If in any doubt as to the handling or processing of the purchased product, our material experts as well as our application and laboratory technicians will help you to the best of their ability. AkzoNobel, of course, guarantees an impeccable quality of its products in its product specifications, yet the use thereof lies entirely within the responsibility of the purchaser. As long as we have not guaranteed - in writing - the specific characteristics and suitability of a product for a contractually agreed purpose, any advice or information given regarding the application or handling, even if the advice or information is given to the best of our knowledge, will not be binding nor will it constitute a warranty. AkzoNobel's liability for the use of its products by its customers is limited in its General Sales and Delivery Conditions, to which the purchaser is hereby referred. The applicable version of the Technical Data Sheet for this product can be downloaded from our websites. Previous versions of the Technical Data Sheets are rendered void with the issue of a new one. Date of issue: 2022-07-07 / 12