

TECHNOLOGIA

PU Akrylowy


RODZAJ PRODUKTU

Lakier nawierzchniowy

OPIS PRODUKTU

Światłotwały dwuskładnikowy rozcieńczalnikowy lakier nawierzchniowy o dobrym wypełnianiu. Produkt ten jest łatwy w szlifowaniu i polerowaniu, nadaje się też do drewna wybielanego. Może być używany jako wykończenie dla Quantum Color QC-T460_xx.

- bardzo przejrzysty, wysoki połysk
- odpowiedni dla drewna wybielanego
- zamknięte pory
- łatwy do szlifowania i polerowania
- nieżółknący
- światłotwały w każdych warunkach



KOLOR

Bezbarwny

POZIOM POŁYSKU (OK.GU @ 60°)

90

5 L

20 L

OKRES PRZECHOWYWANIA

24 miesiące

WARUNKI PRZECHOWYWANIA

Trzymać puszki szczelnie zamknięte, w dobrze wentylowanym pomieszczeniu z kontrolą temperatury pomiędzy 10 a 30°C

ZAWARTOŚĆ CIAŁ STAŁYCH

39% ± 1

GĘSTOŚĆ (CIĘŻAR WŁAŚCIWY)

0,97 +/- 1%

LEPKOŚĆ HANDLOWA

17 ± 2 lepkość handlowa DIN 4 mm

PRZYGOTOWANIE SUBSTRATÓW

	Powierzchnie z surowego drewna.	Zamknąć pory przez powtarzanie nałożenia sealera Quantum, np. QIS160
	Pigmentowane lakiery nawierzchniowe zrobione z Quantum Color	Topcoat musi być nakładany bez szlifowania międzyoperacyjnego po upływie 3 do maksymalnie 8 godzin.

UTWARDZACZ (WAGOWO)

HPU6300	50%	do 4 godzin
---------	-----	-------------

ROZCIEŃCZANIE

TPU 9300-F, szybkoschnący
TPU 9301-S, wolnoschnący

METODA APLIKACJI

Aplikacja natryskiem airmix/airless, aplikacja natryskiem wysoko/niskociśnieniowym

APLIKACJA

Ciśnienie natrysku (bar)	1.5 - 2.0	110 - 130
Rozmiar dyszy (mm)		0.18-0.23
Grubość warstwy (g/m²)	80-120	80-120

CZAS SCHNIĘCIA @ 20°C

Pyłosuchy	Przynajmniej 30 minut
Suchy w dotyku	Przynajmniej 2 godziny
Gotowy do transportu	Przynajmniej 16 godzin
Szlifowalny	Przynajmniej 14 godzin
Polerowalny	Przynajmniej po dwóch dniach

Products from AkzoNobel Wood Coatings are exclusively produced for professional and industrial users, who have a basic knowledge of the handling and application of chemical/technical products for surface design. The processing instructions for reaching the qualities given in the leaflets should be regarded as non-binding recommendations and do not constitute any warranty. These recommendations are based on our experiences, including test series, and should facilitate and promote the work of our clients. Any potential deviation from ideal working conditions is within the responsibility of our clients and may affect the (end) result of the application. The purchaser is not relieved from his duties to inspect the product and its suitability for the surface to be processed, preferably through trial processing. If in any doubt as to the handling or processing of the purchased product, our material experts as well as our application and laboratory technicians will help you to the best of their ability.

AkzoNobel, of course, guarantees an impeccable quality of its products in its product specifications, yet the use thereof lies entirely within the responsibility of the purchaser. As long as we have not guaranteed - in writing - the specific characteristics and suitability of a product for a contractually agreed purpose, any advice or information given regarding the application or handling, even if the advice or information is given to the best of our knowledge, will not be binding nor will it constitute a warranty. AkzoNobel's liability for the use of its products by its customers is limited in its

General Sales and Delivery Conditions, to which the purchaser is hereby referred. The applicable version of the Technical Data Sheet for this product can be downloaded from our websites. Previous versions of the Technical Data Sheets are rendered void with the issue of a new one. Date of issue: 2023-01-27 / 3

NORMY TESTOWE

	DIN 68861/1B Narażenie chemiczne powierzchni meblowych
	Materiały i artykuły w kontakcie z żywnością / plastiki na podstawie UNI EN 1186-5: 2003
	EN 71-3 Migracja rozpuszczalnych metali ciężkich / DIN 53160 Część 1 i 2 Odporność na ślinę i pot
	Tox Control - znak przyznawany niskoemisyjnym lakierom do mebli
	Trudnopalny zgodnie z dyrektywą w sprawie wyposażenia morskiego MED 2014/90/EC.

Products from AkzoNobel Wood Coatings are exclusively produced for professional and industrial users, who have a basic knowledge of the handling and application of chemical/technical products for surface design. The processing instructions for reaching the qualities given in the leaflets should be regarded as non-binding recommendations and do not constitute any warranty. These recommendations are based on our experiences, including test series, and should facilitate and promote the work of our clients. Any potential deviation from ideal working conditions is within the responsibility of our clients and may affect the (end) result of the application. The purchaser is not relieved from his duties to inspect the product and its suitability for the surface to be processed, preferably through trial processing. If in any doubt as to the handling or processing of the purchased product, our material experts as well as our application and laboratory technicians will help you to the best of their ability.

AkzoNobel, of course, guarantees an impeccable quality of its products in its product specifications, yet the use thereof lies entirely within the responsibility of the purchaser. As long as we have not guaranteed – in writing – the specific characteristics and suitability of a product for a contractually agreed purpose, any advice or information given regarding the application or handling, even if the advice or information is given to the best of our knowledge, will not be binding nor will it constitute a warranty. AkzoNobel's liability for the use of its products by its customers is limited in its

General Sales and Delivery Conditions, to which the purchaser is hereby referred. The applicable version of the Technical Data Sheet for this product can be downloaded from our websites. Previous versions of the Technical Data Sheets are rendered void with the issue of a new one. Date of issue: 2023-01-27 / 3