





Product description	
Description	Water-dilutable one-pack pore and surface filler with white pigments.

Range of application	
Description	For filling the pores of coarse-pored veneer and wood and for repairing defects prior to the varnishing with waterborne, pigmented Zweihorn® products.

Product data	
Product code	WSP
Packaging size	400 g
Viscosity at delivery	pasty
Shelf life – Original container unopened	at least 1 year

Preparation of substrates		
	Raw wooden surfaces.	P120, P150, P180

Processing	
	Application is made with a Japan putty knife, so that the pores are filled and that only a few or no material is left on the wood. After drying, depending on the wood pores, another coat must be applied, if required. In the case of large surfaces, quickly apply path by path.

Drying time @ 20°C	
Sandable	at least 3 hours

Aftertreatment	
After sanding with P280-320 grit paper, the surface can be retreated with the same product at any time. After the desired filling result has been obtained, further coating can be made with waterborne Zweihorn® products.	

Products from AkzoNobel Wood Coatings are exclusively produced for professional and industrial users, who have a basic knowledge of the handling and application of chemical/technical products for surface design. The processing instructions for reaching the qualities given in the leaflets should be regarded as non-binding recommendations and do not constitute any warranty. These recommendations are based on our experiences, including test series, and should facilitate and promote the work of our clients. Any potential deviation from ideal working conditions is within the responsibility of our clients and may affect the (end) result of the application. The purchaser is not relieved from his duties to inspect the product and its suitability for the surface to be processed, preferably through trial processing. If in any doubt as to the handling or processing of the purchased product, our material experts as well as our application and laboratory technicians will help you to the best of their ability. AkzoNobel, of course, guarantees an impeccable quality of its products in its product specifications, yet the use thereof lies entirely within the responsibility of the purchaser. As long as we have not guaranteed – in writing – the specific characteristics and suitability of a product for a contractually agreed purpose, any advice or information given regarding the application or handling, even if the advice or information is given to the best of our knowledge, will not be binding nor will it constitute a warranty. AkzoNobel's liability for the use of its products by its customers is limited in its General Sales and Delivery Conditions, to which the purchaser is hereby referred. The applicable version of the Technical Data Sheet for this product can be downloaded from our websites. Previous versions of the Technical Data Sheets are rendered void with the issue of a new one. Date of issue: 2021-07-14 / 7